

Gefen EXT-VGA-KA-LANS-TX VGA KVM over IP Extender (Transmitter) with USB/Audio/RS-232/IR

- Video Input connector (Sender): (1) VGA HD-15, female
- Video Output connector (Sender): (1) VGA HD-15, female
- Video Output connector (Receiver): (1) VGA HD-15, female
- Line Input (Sender): (1) 3.5mm mini-stereo jack
- Line Output (Sender): (1) 3.5mm mini-stereo jack
- Mic Input (Receiver): (1) 3.5mm mini-stereo jack
- Headphones/Line Output (Receiver): (1) 3.5mm mini-stereo jack
- USB Host Interface port (Sender): (1) USB Type B, female
- USB Device ports (Receiver): (2) USB 2.0 Type A, female / (2) USB 1.1 Type A, female
- RS-232 port (Sender): (1) DB-9, female
- RS-232 port (Receiver): (1) DB-9, male
- IR Sensor (Receiver): (1) Located on front panel
- IR In/Ext (Sender/Receiver): (1) 3.5mm mini-stereo jack
- IR Out (Sender/Receiver): (1) 3.5mm mini-mono jack
- IR Extender type EXT-RMT-EXTIRN
- Ethernet port (Sender): (1) RJ-45, shielded, PoE
- Ethernet ports (Receiver): (2) RJ-45, shielded, one with PoE
- Channel Up/USB-Request button (Receiver): (1) tact-type
- Channel Down button (Receiver): (1) tact-type
- Mode button (Sender): (1) tact-type, recessed
- Reset button (Sender/Receiver): (1) tact-type, recessed
- Program button (Sender/Receiver): (1) tact-type, recessed