

Apantac KVM-IP-Tx HDMI/DVI/VGA(DVI-I connector)/USB KVM Extender (Transmitter) over Gigabit Ethernet LAN

MODEL		KVM-IP-Tx
Video	Input	DVI-I (HDMI/DVI+VGA)
	Output	N/A
Audio	Input	3.5mm Stereo phone Jack
	Output	3.5mm Stereo phone Jack
Microphone	Input	N/A
USB	Upstream	USB Type B (Female)
	Downstream	N/A
System Link	Input	N/A
	Output	RJ-45
IR/Frequency		3.5mm stereo phone Jack 20 ~ 60 KHz
RS-232 / Baud Rate		3-pin Pheonix Terminal Block / up to 115,200 bps / Full Duplex
Video Resolution		HDMI/VGA: 1920x1080@60Hz / DVI: 1920x1200@60Hz
Interconnect Cable		Standard CAT6/6a/7 network cable
Maximum cable Length		170m point to point, 100m when working with a switch
Operation Temperature		0 ~ 50°C
Storage Temperature		-20 ~ 85°C
Environment Humdity		0 ~ 80% (Non-condensing)
Power Consumption		400mA
Power Supply		DC 12V, 1.5A
Housing / Color		Metal / Silver
Weight		600g
Dimension		153.4 x 88.2 x 31.5 mm