

Apantac KVM-SET-12-II HDMI/DVI/VGA(DVI-I connector)/USB KVM Extender (Transmitter/Receiver) Kit over Gigabit Ethernet LAN

MODEL		KVM-IP-Tx	KVM-IP-Rx
Video	Input	DVI-I (HDMI/DVI+VGA)	N/A
	Output	N/A	DVI-1 (HDMI/DVI+VGA)
Audio	Input	3.5mm Stereo phone Jack	
	Output	3.5mm Stereo phone Jack	N/A
Microphone	Input	N/A	3.5mm Stereo phone Jack
USB	Upstream	USB Type B (Female)	N/A
	Downstream	N/A	4 USB Type A (Female)
System Link	Input	N/A	RJ-45
	Output	RJ-45	N/A
IR/Frequency		3.5mm stereo phone Jack 20 ~ 60 KHz	
RS-232 / Baud Rate		3-pin Pheonix Terminal Block / up to 115,200 bps / Full Duplex	
Video Resolution		HDMI/VGA: 1920x1080@60Hz / DVI: 1920x1200@60Hz	
Interconnect Cable		Standard CAT6/6a/7 network cable	
Maximum cable Length		170m point to point, 100m when working with a switch	
Operation Temperature		0 ~ 50°C	
Storage Temperature		-20 ~ 85°C	
Environment Humdity		0 ~ 80% (Non-condensing)	
Power Consumption		400mA	400mA
Power Supply		DC 12V, 1.5A	DC 12V, 1.5A
Housing / Color		Metal / Silver	
Weight		600g	600g
Dimension		153.4 x 88.2 x 31.5 mm	153.4 x 88.2 x 31.5 mm