

Electro-Voice EVOLVE50-KIT EVOLVE 50 Portable Column System (Speaker/Subwoofer)/Black/37 Hz-20 KHz

Frequency response (-3 dB) ¹	43 Hz-20 KHz
Frequency range (-10 dB) ¹	37 Hz-20 KHz
Maximum SPL ²	127 dB
Coverage (H x V)	120° x 40°
Amplifier rating	1000 W
LF channel rating	500 W
HF channel rating	500 W
Crossover frequency	200 Hz
Connectors	2x XLR/TRS Combo Jack Input 1x 3.5 mm Input 1x Stereo RCA Input 1x Wireless Bluetooth® Audio Input 1x XLR THRU Output 1x XLR MIX OUT Output
Enclosure	Sub: 15 mm plywood Column: Composite Pole: Aluminum
Grille	Steel with black or white powder coat
Color	Black
Dimensions (HxWxD): mm (in)	Sub: 530 x 345 x 471 (20.9 x 13.6 x 18.5) Column: 825 x 102 x 172 (32.5 x 4.0 x 6.9) Pole: 929 x 48.5 x 55 (36.6 x 1.9 x 2.2)
Net weight	Sub: 44.66 lb (20.3 kg) Column: 10.34 lb (4.7 kg) Pole: 2.75 lb (1.25 kg) Sub cover: 0.9 lb (0.4 kg) Bag for column and pole: 1.87 (0.85 kg)
Shipping weight	Sub box: 50.71 lb (23 kg) Column box: 18.30 lb (8.3 kg)
Power consumption ³	100-240 V AC, 50-60 Hz, 1.5-0.6 A

1. Full-space measurement using music DSP preset.
2. Maximum SPL is measured at 1 m using broadband pink noise at maximum output.
3. Current rating is 1/8 power.