

Apantac Si-16 16x1 VoIP (ST 2022-6)/HDMI/SDI Multiviewer in 1 RU

MODEL	Si-16 Cost-Effective 16x1 IP Multiviewer		
Video Inputs	16 ST-2022-6	Video Outputs	2 identical HDMI, SDI
Connectors	LC/PC multi-mode Fiber	Audio Outputs	AES and embedded SDI and HDMI audio pair monitor outputs
Total Windows	16	Output Resolution	1920 x 1080p 50/60Hz
Supported Resolutions	480i, 576i, 720P, 1080i, 1080P 50/59.94/60Hz	On-Screen Display	Borders, labels, tally UMD, OMD, IMD, dynamic UMD
General Purpose IO	Up to 32 inputs with RJ50 - DB9 connectors	IP	100 Base-Tx, TSL, AXP Connector: RJ45
Serial Port	Connector: RJ45, Baud Rate up to 115200 Format, TSL, TSI, AXP	Electrical	50W, 90-250V 50/60 Hz
Embedded Audio	16 channels	EMI/RFI	Complies with FCC Part 15 Class A, CE, EU EMC, C-tick
Alarms	No audio, audio high/low, no video	Size	1 RU, 25 cm (10")
Power	90-250 AC / 12 DC		