

AJA IPR-10G2-HDMI Single Channel SMPTE ST 2110 Video and Audio IP Decoder to HDMI 1.4b (UltraHD/HD) with hitless switching

Video Formats

- (UltraHD) 3840 x 2160p 23.98, 24, 25, 29.97, 30
- (HD) 1920 x 1080p 23.98, 24, 25, 29.97, 30, 50, 59.94, 60
- (HD) 1920 x 1080i 50, 59.94
- (HD) 1280 x 720p 50, 59.94, 60
- (SD) 625i 50
- (SD) 525i 59.94

Video Quality

- 10-bit, 4:2:2, uncompressed

Discovery, Registration and Control

- NMOS
- Ember Plus (no discovery, control only)

Media Transport Interfaces

- SMPTE ST 2110
 - 2x SFP+ Cages - SFPs not included
- Recommended 10 GigE SFP+ modules:
 - Arista Networks SFP-10G-SR Compatible 10GBASE-SR
 - Fiberstore SFP-10GSR-85 10G SFP+ 850nm
 - Finisar FTLX1471D3BCL (for single mode 1310nm)
 - Mellanox MFM1T02A-SR 850nm 10G

Note: Maximum supported SFP+ power is 500 mWatts per SFP+ cage

Video Input IP

- SMPTE ST 2110
 - Single channel input
 - Dual channel input for hitless switching (based on SMPTE ST 2022-7)

Video Output Digital

- 1x HDMI Standard Type A connector
 - HDMI v1.4b 24/30-bits per pixel, RGB/YUV

Audio Output Digital

- Up to 8-Channel, HDMI embedded audio, 24-bit per channel, 48 kHz synchronous

Audio Output Analog

- 2x RCA analog audio
 - Levels at -10 dBu (nominal)

Reference

- 1x BNC
 - Analog Color Black or HD tri-level sync
 - Reference input is terminated into 75 ohms

User Controls

- 1x RJ-45 for 10/100/1000 Base-T Ethernet
 - Web and REST clients supported
- 1x USB 2.0 Mini-B connector
 - AJA eMini-Setup of network parameters via local desktop computer

Size (w x d x h)

- 5.07" x 0.94" x 5.06" (128.78 x 23.88 x 128.52 mm)

Weight

- 0.6 lb (0.3 kg)

Power

- 5-20VDC Regulated, 13 Watts, Power supply required (DWP-U-R1 included with purchase)

Environment

- Safe Operating Temperature: 0 to 40 C (32 to 104 F)
- Safe Storage Temperature (Power OFF): -40 to 60 C (-40 to 140 F)
- Operating Relative Humidity: 10-90% noncondensing
- Operating Altitude: <3,000 meters (<10,000 feet)