

PreSonus I/O 4 2-Way Small Format Indoor/Outdoor Multi-Tap 100V Passive Speaker/Pair

System Performance	
Frequency Response (-3 dB) *	80 Hz – 18 kHz
Frequency Range (-10 dB)	75 Hz – 19 kHz
Nominal directivity (-6 dB)	Horizontal: 75 Degrees
Nominal directivity (-6 dB)	Vertical: 50 Degrees
Maximum Continuous SPL (passive, @ 1 meter)	105 dB
Power Handling (RMS)**	Noise 50W Maximum 100W
Pressure Sensitivity	2.83V 87 dB (1W, 1M)
Transducers	
Components	LF: 4" (101.6 mm) x 2 HF: 1" Exit (25.4 mm) x 1
Diaphragm	Titanium
Nominal Impedance	8Ω (switchable)
Physical	
Enclosure	Injection-molded, high-impact polycarbonate
Finish Color	Black or White
Grille	Powder-coated steel mesh
Connectors	Push terminal
Transformer	Isolate 5W, 12W, 25W, 50W / 100V
Dimensions	11.9" (303 mm) x 6.2" (157 mm) x 10.5" (267 mm)
Net Weight	11 lbs (5 kg)
Shipping Weight (2 per carton)	24.6 lbs. (11.2 kg)
Product Versions	Ai
Supports	Universal supports
Footnotes	
*	Frequency response and range measured on-axis with anechoic environment.
**	Power handling tested using pink noise filtered to meet IEC 268-5, 6 dB crest factor, 100 hours, with recommended EQ.