

Kramer VSM-4x4A 4x4 Seamless AV Matrix Switcher/Multi-Scaler

INPUTS

- 4 HDMI connectors (HDMI, HDCP version 1.1)

OUTPUTS

- 4 HDMI connectors (HDMI, HDCP version 1.1), 4 balanced stereo audio on terminal block connectors, 4 unbalanced audio on 3.5mm mini jacks

PORTS

- 1 RS-232 on 9-pin connector, 1 Ethernet on RJ-45 connector, 1 USB on Type-A connector

OUTPUT RESOLUTIONS

- NATIVE, 480p, 576p, 720p50, 720p59, 720p60, 1080p24, 1080p50, 1080p60, 1024x768, 1280x800, 1280x1024, 1366x768, 1440x900, 1600x900, 1680x1050 or 1920x1200

VIDEO LATENCY

- Progressive input: 30ms (typical)

CONTROLS

- Front panel buttons, IR with customized remote control, RS-232, Ethernet with built-in Web pages, USB port for programming

POWER SOURCE

- 100–240V AC, 27VA max

OPERATING TEMPERATURE

- 0° to +40°C (32° to 104°F)

STORAGE TEMPERATURE

- -40° to +70°C (-40° to 158°F)

HUMIDITY

- 10% to 90%, RHL non-condensing

INCLUDED ACCESSORIES

- Power cord, rack ears, IR remote control

PRODUCT DIMENSION

- 19" x 7.20 x 1U (43.6cm x 18.30cm 4.36cm) W, D, H

PRODUCT WEIGHT

- 1.8kg (4.0lbs) approx

SHIPPING DIMENSION

- 52.50cm x 33.00cm x 10.70cm (20.67" x 12.99" x 4.21") W, D, H

SHIPPING WEIGHT

- 2.7kg (6.0lbs) approx