

AVPro Edge AC-EX40-444-KIT-b Ultra Slim 40m (70m HD) 4K/60 4x4x4 HDR HDBaseT Extender (Transmitter/Receiver) Kit

Video:	
Video Resolutions	Up to 4K60HZ 4:4:4
VESA Resolutions	Up to DCI 4K (4096x2160)
HDR Formats/Resolutions	420,422,444 (10 and 12 Deep Color)
Color Space	YUV (Component). RGB (CSC: Rec. 601, Rec. 709, BT2020, DCI, P3 D6500)
Chroma Subsampling	4:4:4, 4:2:2, 4:2:0 Supported
Deep Color	Up to 16 bit (1080), Up to 12 bit (4K)
Audio:	
Audio Formats Supported HDMI	PCM 2.0 Ch, LPCM 5.1 & 7.1, Dolby Digital, DTS 5.1, Dolby Digital Plus, Dolby TrueHD, DTS-HD Master Audio. DTS-X,
Audio Formats Supported Extracted (2CH Port)	PCM 2 CH (No Downmix)
Distance:	
HDBaseT (CAT) Distance (4K)	40M (131 Feet)
HDBaseT (CAT) Distance (Full HD)	70M (230 Feet)
HDMI Lead In/Out (up to 4K60 4:4:4)	Up to 50 Feet (Bullet Train HDMI)
HDMI Lead In/Out (w/ AOC Cable) (up to 4K60 4:4:4)	Up to 130 Feet (w/ Bullet Train AOC)
Other:	
Bandwidth	18 Gbps (w/ ICT)
HDCP	HDCP 2.2 and Earlier
Ports:	
HDMI (Tx&RX)	Type A
Audio (Extracted Analog) (Tx & RX)	3 pin terminal block (unbalanced)
IRTx (Tx & RX)	3.5mm Mono (2 Conductor)
IR Rx (Tx & RX)	3.5mm Stereo (3 Conductor)
RS232 (Tx & RX)	3 pin terminal block
Power (Tx & Rx)	2 pin terminal block
Environmental:	
Operating Temperature	23 to 125°F (-5 to 51°C)
Storage Temperature	-4 to 140°F (-20 to 60°C)
Humidity Range	5-90% RH (No Condensation)
Power:	
Power Consumption (Total)	9 Watts Max Pair
Power Supply	Input: AC 100-240V ~ 50/60HZ Output: DC 48V .5A (Wall Version)
Dimensions:	
Dimensions (Single Unit Only, Tx or Rx are same) (Length/Width/Height) (Tx or Rx each alone)	mm: 381x 231 x 12 inch: 15 x 9.1 x .48
Dimensions (Packaged Length/Width/Height) (Kit)	mm: 138 x 165 x 91 inch: 5.5 x 6.5 x 3.6
Weight (Unit) (Tx or Rx each alone)	.3lbs (. 13Kg)
Weight (Packaged)	2lbs (.90Kg)
* Specifications subject to change without notice. Mass & dimensions are approximate	