

Kramer VP-211K-b 2x1 VGA Video and Stereo Audio Standby Switcher

| | |
|----------------------------|---|
| INPUTS: | 2 computer graphics video on 15-pin HD connectors; 2 unbalanced stereo audio on 3.5mm mini jacks. |
| OUTPUTS: | 1 computer graphics video on a 15-pin HD connector; 1 computer graphics video looping on a 15-pin HD connector; 1 unbalanced stereo audio on a 3.5mm mini jack. |
| MAX. OUTPUT LEVEL: | Video: 1.6Vpp; Audio: >10.5Vpp. |
| BANDWIDTH (-3dB): | Video: 300MHz; Audio: >100kHz. |
| DIFF. GAIN: | 0.03%. |
| DIFF. PHASE: | 0.03Deg. |
| K-FACTOR: | <0.05%. |
| S/N RATIO: | Video: 71dB; Audio: 71dB weighted. |
| CROSSTALK: | Video: -59dB @5MHz; Audio: <-66dB @1kHz. |
| CONTROLS: | Contact closure remote control, input default selection switch. |
| COUPLING: | DC. |
| AUDIO THD + NOISE: | <0.032%. |
| AUDIO 2nd HARMONIC: | <0.004%. |
| POWER SOURCE: | 5V DC 200mA. |
| DIMENSIONS: | 12.1cm x 7.18cm x 2.42cm (4.76" x 2.83" x 0.95") W, D, H. |
| WEIGHT: | 0.3kg (0.66lbs) approx. |
| ACCESSORIES: | Power supply, mounting bracket. |
| OPTIONS: | RK-3T 19" rack adapter. |