

Bolin Technology VCC-8-4K20S-3SMB 4K PTZ SDI/HDMI/HDBaseT Camera with 20x Optical and 12X Digital Zoom

Image Sensor	1/2.5 inch CMOS 8.5MP
Lens	Optical Zoom 20X, F=4.4(W)~88.4mm(TELE)
SRZ Zoom	Up to 30X in 4K and 40X in Full HD with SRZ(Super Resolution Zoom) feature
Horizontal Angle of View	70.2°(W)~4.1°(T)
Min. Illumination	0.4lux (1/30s, 50%, High Sensitivity mode On), 1.6lux (1/30s, 50%, High Sensitivity mode Off), 0.06lux(1/4s(1/3s),50%, High Sensitivity mode On), 0.21lux(1/4s(1/3s),50%, High Sensitivity mode Off)
Image Stabilization	YES
HDMI Output	4K 2160p:29.97/25/23.98; 1080p:59.94/50/29.97/25; 1080i:59.94/50; 720p:59.94/50/23.98 (23.98 supported via FW upgrade)
Frame Rate	23.98 Frame Rate supported via FW upgrade
SDI Output	1080p:59.94/50/29.94/25/23.98; 1080i:59.94/50; 720p:59.94/50
HDBaseT Output	4K 2160p:25/29.97; 1080p:59.94/50; 1080i:59.94/50; 720p:59.94/50
CVBS	720*576i50
Availability	HDBaseT receiver sold separately.
Input / Interface	HDBaseT, RJ45
Output	HDMI 1.4 (4K), IP Pass-Through supports IP control and IP video streaming. (Not an IP encoder)
Control Interface	RS232/RS422/RS485(RJ45 Ports), IR Receiver
Power Input	DC12V
Power Output	Provides power to camera over Cate5e/6 cable
Dimension	164x118x33mm
Weight	0.52kg
Gross Weight (Approximate)	1KG/2.2LBS
Packing Dimension (Approximate)	cm: W22XD18XH10; Inch: W8.8XD7XH4
Pan Movement	Horizontal:±350 degrees continuous pan (Zoom Adaptive Speed Range: 0.05°■100°/S)
Tilt Movement	Vertical:+90 degrees to -30 degrees (Zoom Adaptive Speed Range: 0.05°■50°/S)
Preset Position	128■Speed adjustable: Up to 150°/S, 6 presets on remote controller), 0~5 Level Adjustable
Video Output 1	,1XRJ45-HDBaseT(4K), With HDBaseT video output distance up to 100 meters
Video Output 2	1XHDMI Type A- HDMI1.4(4K), 1XBNC-3G-SDI(1080P), 1XCVBS.
Control Interface	2XRJ45-RS232/RS422/RS485 (Phoenix Connection adapter included), IR Remote Control Sensor
Control Protocol	VISCA / Pelco P,D
SDI Standard	Supports SD-SDI, HD-SDI, 3G-SDI
Signal Format	1080p:59.94/50/29.94/25/23.98; 1080i:59.94/50; 720p:59.94/50
Standard	SMPTE 292, SMPTE 424, SMPTE 425-A (With SMPTE352 SDI Metadata Supported)
Operating Temperature	-10 to +50 (°C)
Power Input	DC12V, POH (Power Over HDBaseT)
Power Consumption	9.6W
Dimension	260x145x192mm
Weight	2.7kg
Gross Weight (Approximate)	4KG/8.8LBS
Packing Dimension (Approximate)	cm: W30XD24XH31; Inch: W12XD10XH12