

Apantac MI-16+ Cost effective Dual Output (8+8) Multiviewer

Cost effective Dual Output (8+8) Multiviewer

Features:

- Low latency - single frame processing delay
- Low Energy - only uses 15 W of power
- Accepts 16 auto-detect 3G/HD/SD-SDI inputs
- 16 Passive input loop through
- Windows can be sized and moved freely
- Decode up to 16 embedded audio per SDI input
- Total of 128 audio meters (64 meters per output)
- 2 separate independent outputs with 8 inputs each
- Simultaneous HDMI and SDI outputs
- Ethernet for configuration and external control
- Dynamic UMD/labels & Tallies (TSL)
- Stand alone labels, customizable logos
- 32 GPIs for tallies, count up/down triggers or alarms
- 2 digital and 2 analog clocks can be sync'd with LTC or NTP
- Borders can be turned on or off
- Safe area markers
- Visual Alarm tags for video/audio alarm detection
- Stereo analog audio monitoring output
- Optional redundant power supply
- 3 year limited warranty

Accessories

Standard

- Rack mount
- 4 x RJ50 to DB9 for GPI
- 4 x breakout terminal blocks
- RJ45 to DB9 for serial
- Analog audio breakout cable
- CD (software, manual)

Options

- Redundant power supply