

Kramer VP-747 & VP-747T 8x2:3 Scaler Seamless Switcher & Remote Console w T-Bar

VP-747

INPUT:	2 HDMI/DVI on DVI connectors (HDMI, HDCP 1.2); 8 sets of universal BNC connectors: R/Pr, G/Y/CV, B/Pb/C, Hs/Cs, and Vs, each programmable for use as CV, Y/C, RGB, YCbCr, YPbPr, RGBS or RGBHV.
PREVIEW OUTPUT:	1 HDMI/DVI on DVI connector (HDMI, HDCP 1.2), 1 UXGA on a 15-pin HD (F) connector, 1 RGBHV/YPbPr on BNC connectors.
PROGRAM OUTPUT:	1 HDMI/DVI on DVI connector (HDMI, HDCP 1.2), 1 UXGA on a 15-pin HD (F) connector, 1 RGBHV/YPbPr on BNC connectors.
COMPUTER OUTPUT RESOLUTIONS:	640x480 60Hz, 640x480 75Hz, 800x600 50Hz, 800x600 60Hz, 800x600 75Hz, 832x624 75Hz, 852x480 60Hz, 1024x768 50Hz, 1024x768 60Hz, 1024x768 75Hz, 1280x720 60Hz, 1280x768 50Hz, 1280x768 60Hz, 1280x800 60Hz, 1280x1024 50Hz, 1280x1024 60Hz, 1280x1024 75Hz, 1366x768 50Hz, 1366x768 60Hz, 1400x1050 50Hz, 1400x1050 60Hz, 1440x900 60Hz, 1600x1200 50Hz, 1600x1200 60Hz, 1680x1050 60Hz, 1920x1080 50Hz, 1920x1080 60Hz, 1920x1200 60Hz, 480px60Hz, 576p, 720p 50Hz, 720p 60Hz, 1080i 50Hz, 1080i 60Hz, 1080p 50Hz, 1080p 60Hz, 1080p 24Hz (for HDMI), 480px59.94Hz, 720px59.94Hz, 1080ix59.94Hz, 1080px23.97Hz, 1080px29.97Hz, 1080px59.94Hz or one of 4 Custom resolutions
HDTV OUTPUT RESOLUTIONS:	480px60Hz, 576px60Hz, 720px50Hz, 720px60Hz, 1080ix50Hz, 1080ix60Hz, 1080px50Hz, 1080px60Hz, 1080p@24Hz,
CONTROLS:	Front panel buttons, high-contrast LCD, IR remote control, Ethernet, audio control, RS-232, RS-485, and optional T-bar remote controller.
ADDITIONAL CONTROLS:	Freeze, zoom, different selectable vertical refresh rates, ProcAmp control, output image scaling, Picture-In-Picture and aspect ratio change.
POWER CONSUMPTION:	100-240V AC, 50/60HZ, 55VA.
DIMENSIONS:	19" x 9.3" x 3U W, D, H, rack mountable.
WEIGHT:	5.5kg (12.2lbs) approx.
INCLUDED ACCESSORIES:	IR remote control, power cord, rack "ears", and null-modem adapter.
OPTIONS:	VP-7471 remote control console.

VP-747T

PORTS:	2 sets of RS-485 on 3-pin terminal block connectors, 2 sets of RS-485 on mini-XLR connectors.
CONTROLS:	Front panel buttons, RS-232, and RS-485.
POWER CONSUMPTION:	12V DC, 280mA.
DIMENSIONS:	19" x 7" x 4U W, D, H, rack mountable.
WEIGHT:	1.58kg (3.5lbs) approx.
ACCESSORIES:	Gooseneck lamp, 2 mini XLR connectors, power supply, rack "ears", table top brackets.