

## Aten CS9138 8-Port PS/2 VGA KVM Switch

<b>Computer Connections</b>	
Direct	8
Maximum	512 (via Cascade)
Port Selection	OSD, Hotkey, Pushbutton
<b>Connectors</b>	
Console Ports	1 x HDB-15 Female (Blue) 1 x 6-pin Mini-DIN Female (Purple) 1 x 6-pin Mini-DIN Female (Green)
KVM Ports	8 x HDB-15 Male (Blue) 8 x 6-pin Mini-DIN Female (Purple) 8 x 6-pin Mini-DIN Female (Green)
Power	1 x DC Jack (Black)
<b>Switches</b>	
Power	8 x Pushbutton
<b>LEDs</b>	
Online	8 (Green)
Selected	8 (Orange)
Power	1 (Blue)
<b>Emulation</b>	
Keyboard / Mouse	PS/2
Video	1920 x 1440; DDC2B
Scan Interval	3, 5, 10, 15, 20, 30, 40, 60 seconds
Power Consumption	DC9V:1.5W:7BTU
<b>Environmental</b>	
Operating Temperature	0-50°C
Storage Temperature	-20-60°C
Humidity	0-80% RH, Non-condensing
<b>Physical Properties</b>	
Housing	Metal
Weight	2.85 kg ( 6.28 lb )
Dimensions (L x W x H)	43.72 x 16.29 x 4.40 cm (17.21 x 6.41 x 1.73 in.)
Note	For some of rack mount products, please note that the standard physical dimensions of WxDxH are expressed using a LxWxH format.