

# Avenview HDM2-SPLITPRO-T4K 4x1 HDMI 2.0 Quad Multiviewer with 4K/60 UHD Scaler

ITEM	DESCRIPTION
UNIT	HDM2-SPLITPRO-T4K
UNIT DESCRIPTION	4x1 HDMI 2.0 Quad multiviewer with Rotation, 4K@60 support on output
HDCP COMPLIANCE	Yes 2.2
VIDEO BANDWIDTH	Input: HDMI [2.25G to 6.75Gbps] / Output: Single-link 600MHz [18Gbps]
HDMI COMPLIANCE	Input: HDMI 1.4 /Output: HDMI 2.0a
VIDEO FORMAT SUPPORT	HDMI 2.0
INPUT SUPPORTED RESOLUTIONS	PC -VGA 640x480, XGA (1024 x 768), SXGA (1280 x 1024), UXGA (1600 x 1200), WUXGA (1920 x 1200) 480i/720p/1080i/1080p@60 and up to 1920x1200@60
OUTPUT SUPPORTED RESOLUTIONS	720p 50Hz, 720p 60Hz, 1080p 24Hz, 1080p 25Hz, 1080p 30Hz, 1080p 50Hz, 1080p 60Hz, 1920X1200RB Hz, 3840x2160 60 Hz and 4K2K@60 (4:4:4 8bits)
AUDIO SUPPORT	LPCM 2CH, 6CH, 8CH/AC3/DTS/Dolby Digital Plus/ Dolby TruHD & DTS-HD
INPUT	4x HDMI + 1xRS-232 + 1x RJ-45(Ethernet)
OUTPUT	1 x HDMI
CONTROL	RS 232 / IP Control
RJ45 CONNECTOR	WE/SS 8P8C with 2 LED indicators
ESD PROTECTION	Human body model — ±15kV [air-gap discharge] & ±8kV [contact discharge]
WEIGHT	3.3 lbs
DIMENSIONS (L X W X H)	12.5" x 6.8" x 1.7"
POWER SUPPLY	12V/5A DC (US/EU standards, CE/FCC/UL certified)
POWER CONSUMPTION	8.9W
ENVIRONMENTAL	
OPERATING TEMPERATURE	32~104 F (0~40 C)
STORAGE TEMPERATURE	-4~140 F (-20~60 C)
RELATIVE HUMIDITY	20~90% RH (no condensation)