

Avenview SW-HDM2-T4K-4X1 4x1 4K HDMI2.0/HDCP2.2 Switcher with HDR10 IR/RS232/Telnet and Web GUI

ITEM	DESCRIPTION
UNIT	SW-HDM2-T4K-4X1
UNIT DESCRIPTION	4X1 4K@60/ UHD HDMI Switcher with IR/RS-232/ Support
HDCP	YES
VIDEO BANDWIDTH	600 MHz (6 Gbps)
SUPPORTED RESOLUTION	480i~UHD (3840x2160@24/25/30/50/60 & 4K (4096x2160@24/25/30/50/60Hz)
AUDIO SUPPORT	PCM 2/5.1/7.1CH, Dolby Digital 2~5.1CH, DTS 2~5.1CH, Dolby Digital Plus, Dolby TrueHD, Dolby Atmos and DTS-HD Master Audio
ESD PROTECTION	Human body model — ± 12kV (air-gap discharge) & ±8kV (contact discharge)
INPUT	4 x HDMI 1 x IR 1 x RS 232 1 x ETHERNET 1 x USB (Factory use)
OUTPUT	1 x HDMI
HDMI CONNECTOR	Type A (19 pin female) Sampling Rate 32kHz ~ 192 kHz
IR FREQUENCY	38kHz
DIMENSIONS (L X W X H)	9.4" x 4.0" x 1.7" 240 mm (L) x 104 mm (W) x 43mm (H)
WEIGHT	0.79kg /1.74lbs
POWER SUPPLY	5VDC /2.6A (US/EU standards, CE/FCC/UL certified)
POWER CONSUMPTION	5.83W Standby Mode (1.1W)
ENVIRONMENTAL	
OPERATING TEMPERATURE	32° ~ 104°F (0° to 40°C)
STORAGE TEMPERATURE	-4° ~ 140°F (-20° ~ 60°C)
RELATIVE HUMIDITY	20~90% RH (no condensation)