

ClearView PantherView08HD-4D-Tri-Kit 8 Channel HD-AVS DVR PantherView Kit 4 Dome 1080P Cameras with 1 TB

Main Processor:	Embedded Linux processor
Video Input:	8 channel BNC
HD-AVS:	1080P/720P HDCVI Camera
IP:	Support 2ch 1080P/720P IP Camera
Display Interface:	1 HDMI, 1 VGA
Resolution:	1920x1080, 1280x1024, 1280x720, 1024x768
Display Split:	1/4/8/9
Privacy Masking:	4 rectangular zones (each camera)
OSD:	Title, Time, Video loss, lock, Motion detection, Recording
Recording Video/Audio Compression:	H.264/G.711
Main Stream:	1080P(1~15fps)/720P/960H/D1 (1~25/30fps)
Extra Stream:	CIF/QCIF(1~25/30fps), D1
Bit Rate:	96~4096Kb/s
Record Mode:	Manual, Schedule(Continuous, MD), Stop
Record Interval:	1~60 min, Pre: 1~30 sec, Post: 10~300 sec
Trigger Events:	Recording, PTZ, Tour, Alarm out, Video Push, Email, FTP, Snapshot, Buzzer & Screen tips
Video Detection:	Motion Detection, MD Zones: 396(22x18), Video Loss & Camera Blank
Alarm Input:	8 channel
Relay Output:	3 channel
Audio Input:	4 channel, RCA
Audio Output:	1 channel, RCA
Two-way Talk:	Reuse audio input/output channel 1
Sync Playback:	1/4/9
Search Mode:	Time/Date, MD & Exact search (to second)
Playback Functions:	Play, Pause, Stop, Rewind, Fast play, Slow play, Next file, Previous file, Next camera, Previous camera, Full screen, Repeat, Shuffle, Backup selection, Digital zoom
Backup Mode:	USB Device/Internal SATA burner/Network
Ethernet:	RJ-45 port (10/100M)
Network Functions:	HTTP, IPv4/IPv6, TCP/IP, UPNP, RTSP, UDP, SMTP, NTP, DHCP, DNS, PPPOE, DDNS, FTP, IP Filter, SNMP, P2P
Max. User Access:	128 users
Internal HDD:	2 SATA ports, up to 8TB
USB Interface:	2 ports(1 Rear), USB2.0
RS485:	1 port, For PTZ control
Power Supply:	DC12V/4A, 15W
Working Environment:	-10°C ~+55°C / 10%~90%RH
Dimension:	14.76"x11.22"x2.16"
Weight:	5.18 lbs (without HDD)