

KanexPro SW-HD20-5X14K True 4K HDMI 5X1 Switcher with HDCP2.2

Signal Input/Outputs:

- Input DDC Signal: 5 Volts p-p (TTL)
- Input & Output Signal: High Speed HDMI Spec 2.0a

Input Ports: 5 x HDMI (Female)

Output Port: 1 x HDMI (Female)

Operating Frequency: Vertical Frequency Range: 50/60Hz

Supported Resolutions:

- (HDTV) Interlaced (50&60Hz): 480i, 576i, 1080i
- Progressive (50&60Hz): 480p, 576p, 720p, 1080p & 4K@30Hz
- 480i ~1080p50/60, 4Kx2K@24/30
- VGA~UXGA

IR specs: Input Port: 1x IR Receive port

Power Requirements:

- Power Consumption: 2W
- External Power Supply: 5V DC @ 1A

Regulatory Approvals:

- Converter Unit: FCC, Ce, UL
- Power Supply: UL, Ce, FCC

Environment Operating Temperature:

- Operating Temperature: 0°C ~ 40°C / 32°F ~ 104°F
- Storage Temperature: -20°C ~ 60°C / -4°F ~ 140°F

Dimensions: W 2.51" x D 6.1" x H 0.67"

Weight: 6.35 oz. (180g)