

# ICRealtime ICIP-D2000VIR-B-D 2 Megapixel Indoor/Outdoor Full-Size IR Dome IP Camera/3-9mm motorized Lens

<b>Camera</b>	
Image Sensor	1/2.8" 2Megapixel progressive scan Exmor CMOS
Effective Pixels	1920(H)x1080(V)
Scanning system	Progressive
Electronic Shutter Speed	Auto/Manual 1/4-1/10000
Min. Illumination	0.1 lux/F1,4(color), 0Lux/F1,4(IR on)
S/N Ratio	>50dB
Video Output	1 port
<b>Camera Features</b>	
Max IR LEDs Length	60Ft 20m
Day/Night	Auto (ICR) / Color / BAA/
Backlight Compensation	BLC / HLC / DWDR
White Balance	Auto
Gain Control	Auto / Manual
Noise Reduction	3D
Privacy Masking	Up to 4 areas
<b>Lens</b>	
Focal Length	3-9mm motorized
Max Aperture	F1.2
Focus Control	Auto
Angle of View	H: 103.9°(Wide)~34.1°(Tele)
Lens Type	Motorized /Auto Iris(DC)
Mount Type	Board-in Type
<b>Video</b>	
Compression	H.264/MJPEG
Resolution	1080P(1920 *1080) /720P(1280 *720) / D1 (704 x480) / CIF(352 x240)
Frame Rate	Main Stream: 1080P/720P(1 ~ 25/30fps) Extra / Sub Stream: D1/CIF(1 ~ 25/30fps)
Bit Rate	H.264: 32K - 8192Kbps, MJPEG: 32K - 20480Kbps
<b>Audio</b>	
Compression	G.711a /G.711u /PCM
Interface	1/1 channel In/Out
<b>Audio</b>	
Compression	G.711a /G.711u /PCM
Interface	1/1 channel In/Out
<b>Network</b>	
Ethernet	RJ-45 (10/100Base-T)
WiFi	N/A
Protocol	IPv4/IPv6, HTTP, HTTPS, SSL, TCP/IP, UDP, UPnP, ICMP, IGMP, SNMP, RTSP, RTP, SMTP, NTP, DHCP, DNS, PPPOE, DDNS, FTP, IP Filter, QoS, Bonjour
Compatibility	ONVIF, CGI
Max. User Access	20
Smart Phone	iPhone, iPad, Android, Windows Phone
<b>Auxiliary Interface</b>	
Memory Slot	Micro SD, Max 64GB
Alarm	1/1 channel In/Out
<b>General</b>	
Power Supply	DC12V, PoE (802.3af)

Power Consumption	<8.5W
Working Environment	-20°C ~ 60°C/-4°F ~ 140°F, Less than 90% RH
Ingress Protection	IP66
Vandal Resistance	IK10
Dimensions	Φ5.94"x4.68"TT ~ 0151mmx119mm
Weight	3.3lb/1,25kg