

ICRealtime IHX-C1202B 1.3MP Intercom Master Station For 1000 VTH Monitors/Black

Model	IHX-C1202B
System	
Main Processor	Embedded micro processor
Operation System	Embedded LINUX OS
Video	
Video Compression Standard	H.264
Input/Approaching Induction	1.3 megapixel CMOS camera
Black Light	Support
Auto Light Compensation	Support
Audio	
Audio Input	Microphone
Audio Output	Built-in speaker
Bidirectional Talk	Support dual-way bidirectional talk
Display	
LCD Dimensions	3in STN screen
Resolution	128*64
Operation Mode	
Input	Touch keyboard
Card	Built-in IC card induction reader
Approaching Induction	
Body Approaching	3ft
Alarm	
Vandal proof	Support
Access Control	
No Output	Support
NC Output	Support
Door on/off Button	Support
Door Status Detect	Support
Network	
Ethernet	10M/100Mbps Self-adaptive
Network Protocol	TCP/IP
Storage	
Memory	128MB
General	
Power	DC 10~15V
Power Consumption	Standby \approx 1W, work \approx 10W
Working Environments	(-40 \AA \AA \AA 60 \AA \AA) 10%~95%RH
Weather Rated	IP65
Dimensions	(408.0mm*150.0mm*59.1mm)
Weight	lb (1.6Kg)

