ICRealtime NVR-M704GCW 4 Channel Mobile NVR/Integrated 4 Port POE Switch/WIFI Capable/500GB HDD Included

Model	NVR-M704GCW
Syst	tem
Main Processor	Dual-core embedded processor
Operating System	Embedded LINUX
Vid	leo
IP Camera Input	4 channel
Standard	NTSC, PAL
Auc	dio
Input	4 channel
	1 channel
·	1 channel Input, 1 channel Output (aviation connector)
Disp	
	1 VGA, 2 TV
	1920x1080, 1280x1024, 1280x720, 1024x768
	1/4
	Camera title, Time, Video loss, Camera lock, Motion detection, Recording
	<u> </u>
Recoi	
·	H.264 / MJPEG
	1080P(1920x1080) / 720P(1280x720) / D1 (704x576/704x480)
	100/120fps@1080P
	48 ~ 8192kbps
Record Mode	Manual, Schedule(Regular(Continuous), MD, Alarm), Stop
Record Interval	1~120 min (default: 60 min), Pre-record: 1~30 sec, Post-record: 10~300 sec
Video Detect	tion & Alarm
Trigger Events	Recording, PTZ, Tour, Alarm, Video Push, Email, FTP, Buzzer & Screen tips
Video Detection	Motion Detection, MD Zones: 396(22x18), Video Loss & Camera Blank
Alarm Input	8 channel
Relay Output	3 channel
Playback	& Backup
Sync Playback	1/4
Search Mode	Time/Date, Alarm, MD & Exact search (accurate to second), Smart search
Playback Function	Play, Pause, Stop, Rewind, Fast play, Slow play, Next file, Previous file, Next camera, Previous camera, Full screen, Repeat, Shuffle, Backup selection, Digital zoom
Backup Mode	USB Device / Network
Netw	vork
Ethernet	RJ-45 port (10/100M/1000M)
Wireless Network	Built-in 3G / Wi-Fi module
GPS	Built-in high accurate GPS module
Network Function	HTTP, IPv4, TCP/IP, RTSP, UDP, SMTP, NTP, DHCP, DNS, DDNS, FTP, IP Filter
Max. User Access	10 users
Storage	
Internal HDD	2 SATA ports
Auxiliary Interface	
	2 ports (1 Rear), USB2.0
RS232	1 port
RS485	1 port

eSATA	1 port
Memory Slot	SD card, Max.32GB
General	
Power Supply	NVR: 6V~36V
Power Consumption	≤10W
Working Environment	14°F~131°F/-10°C~+55°C / 10~90%RH / 86~106kpa
Dimension(WxDxH)	180mmx208mmx100mm
Weight	3KG(without HDD)