

dARTS 660 In-Wall 6.5 inch Woofers In-Wall Speakers Kit

Specifications	
Frequency Response (± 3 dB)	20 Hz - 20 kHz
Possible Configurations	Scalable from 5.1 to 9.2.4 or higher multi-channel systems
Total System Power	250 W x16 (500 W /speaker)
Subwoofer Power (Peak)	1500 W x2
Minimum SPL (8,000 sq.ft)	105 dB (THX Reference Level)
Dimensions (LCR's)	23.5" H x 14" W x 3.5" D
Cutout Dimensions (Center)	22.375.125" H x 13" W
Dimensions (Surrounds)	23.5" H x 14" W x 3.5" D
Cutout Dimensions (Surrounds)	22.375.125" H x 13" W
Dimensions (DCB 112 Subwoofer)	15.5" H x 14.5" W x 15" D
Dimensions (DCB 210 Subwoofer)	28" H x 14" W x 17" D
Dimensions (DCB 115 Subwoofer)	19.5" H x 15.25" W x 22.4" D
Optional Accessory	Rough-In Bracket (RB-15)

DIW-660-LCR

Left, Center and Right Front Speakers

- **Tweeter:** 1.125" Soft Dome
- **Woofers:** (2) 6.50" Glass Fiber/Nomex Honeycomb/Glass
- **Fiber Dimensions:** 23.50" H x 14.00" W x 3.50" D Cutout
- **Dimensions:** 22.375" H x 13.00" W

DP4000 IA

Class D 16-Channel Digital Amplifier/ Controller

- **Crossover:** DSP based, adaptive
- **Frequency Response within ± 0.5 dB of reference:** 20 Hz - 20 kHz; ± 0.5 dB
- **Harmonic Distortion:** 0.05% (@ 1 kHz)
- **Power Output:** 125 w/ch @ 8 Ω ; 250 w/ch @ 4 Ω
- **Inputs:** 8 balanced (XLR), 16 unbalanced (RCA)
- **Power Requirements:** 120/240V; 50/60 Hz
- **Programming Port:** USB