

## Aten VM5404D 4x4 DVI Matrix Switch with Scaler

|                            |  |
|----------------------------|--|
| Video Input                |  |
| Interfaces                 | 4 x DVI-D Female (White)   |
| Impedance                  | 100 Ω  |
| Max. Distance              | 1.8 m  |
| Video Output               |  |
| Interfaces                 | 4 x DVI-D Female (White)   |
| Impedance                  | 100 Ω  |
| Video                      |  |
| Max. Data Rate             | 6.75 Gbps (2.25 Gbps Per Lane)   |
| Max. Pixel Clock           | 225 MHz  |
| Compliance                 | HDCP 1.4 Compatible  |
| Max. Resolution            | Up to 1920 x 1200  |
| Max. Distance              | Up to 5m   |
| Control                    |  |
| RS-232                     | Connector: 1 x DB-9 Female (Black)<br>Baud Rate and Protocol: Baud Rate: 19200, Data Bits: 8, Stop Bit: 1,<br>Parity: No, Flow Control: No |
| IR                         | 1 x Mini Stereo Jack Female (Black)  |
| Ethernet                   | 1 x RJ-45 Female (Black)   |
| EDID Settings              | EDID Mode: Default / Port 1/ Remix / Customized  |
| Power                      |  |
| Connectors                 | 1 x 3-Prong AC Socket  |
| Maximum Input Power Rating | 100-240VAC; 50-60Hz; 1.0A  |
| Consumption                | 120VAC, 34.1W; 230VAC, 34.4W   |
| Environmental              |  |
| Operating Temperature      | 0-50°C   |
| Storage Temperature        | -20 - 60°C   |
| Humidity                   | 0 - 80% RH, Non-Condensing   |
| Physical Properties        |  |
| Housing                    | Metal  |
| Weight                     | 3.50 kg ( 7.71 lb )  |
| Dimensions (L x W x H)     | 43.24 x 25.98 x 4.40 cm<br>(17.02 x 10.23 x 1.73 in.)  |
| Note                       | For some of rack mount products, please note that the standard physical dimensions of WxDxH are expressed using a LxWxH format.            |