

## Aten VM5808H 8x8 HDMI Scaling Matrix Switcher and Video Wall with Fast Switching

Video Input	Interface	8 x HDMI Type A Female (Black)
	Impedance	100 ?
	Max Distance	1.8 m
Video Output	Interface	8 x HDMI Type A Female (Black)
	Impedance	100 ?
	Max Distance	15 m
Video	Max. Data Rate	6.75 Gbps (2.25 Gbps Per Lane)
	Max. Pixel Clock	225 MHz
	Compliance	HDMI (3D, Deep Color) HDCP 1.4 Compatible Consumer Electronics Control (CEC)
	Max Resolutions	Up to 1080p
	Max Distance	Up to 15 m
Control	RS-232	Connector: 1 x DB-9 Female (Black) Baud rate and protocol: Baud Rate: 19200, Data Bits: 8, Stop Bits:1, Parity: No, Flow Control: No
	IR	1 x Mini Stereo Jack Female (Black)
EDID Settings	EDID Mode: Default / Port1 / Remix / Customized (EDID Wizard support)	
Power	Connector: 1 x 3-Prong AC Socket I/P Rating: 100-240 VAC; 50-60 Hz; 1.0A Consumption: 120 VAC, 60W; 230 VAC, 62W	
Environment	Operating Temp.	0-50°C
	Storage Temp.	-20 - 60°C
	Humidity	0-80% RH, Non-Condensing
Physical Properties	Housing	Metal
	Weight	4.03 kg
	Dimensions (L x W x H)	43.20 x 26.20 x 4.40 cm
Carton Lot	1 pc	