

Aten VS1814T 4-Port HDMI Over Single Cat 5 Splitter

Video Input	Interface	1 x HDMI Type A Female (Black)
	Impedance	100 ?
	Max Distance	1.8 m
Video Output	Interface	1 x HDMI Type A Female (Black) - Local Output 4 x RJ-45 Female
	Impedance	100 ?
Video	Max. Data Rate	10.2 Gbps (3.4 Gbps Per Lane)
	Max. Pixel Clock	340 MHz
	Compliance	HDMI (3D, Deep Color, 4K) HDCP Compatible Consumer Electronics Control (CEC) HDBaseT Compatible
	Max Resolutions	Up to 4K (Depends on connected receiver)
	Max Distance	Up to 100 m (Depends on connected receiver)
Audio	Input	1 x HDMI Type A Female (Black)
	Output	1 x HDMI Type A Female (Black)
Control	RS-232	Connector: 1 x DB-9 Female (Black) Serial Control Pin Configurations: Pin2 = Tx, Pin 3=Rx, Pin 5= Gnd Baud Rate and Protocol: Baud Rate: 19200, Data Bits: 8, Stop Bits:1, Parity: No, Flow Control: No
EDID Settings		EDID Mode: Default / Port 1 / Auto / Learn
Power		Connector: 1 x 3-Prong AC Socket (Black) Consumption:120 VAC, 20W; 230 VAC, 23W
Environment	Operating Temp.	0-50°C
	Storage Temp.	-20 - 60°C
	Humidity	0-80% RH, Non-Condensing
Physical Properties	Housing	Metal
	Weight	2.10 kg
	Dimensions (L x W x H)	43.24 x 26.11 x 4.40 cm
Carton Lot		1 pcs