

## PureLink VIP-200 Tx/Rx HDMI and USB/KVM over IP Extension (Transmitter/Receiver) System

General Technical Specification of VIP200	
SUPPORT RESOLUTION	480i / 480p / 720p / 1080i / 1080p @ 24Hz25Hz30Hz50Hz60Hz
TRANSMISSION DISTANCE	CAT.5e150M / CAT.6180M (Max)
USB CONNECTOR	USB Type A x 4
RS232 CONNECTOR	DB9 (Male) x 1
VIDEO OUTPUT	HDMI Type A x 1
LINK CONNECTOR	RJ45 x 1
AUDIO CONNECTOR	3.5 mm Phone Jack x 2 (10K $\Omega$ / 1Vpp)
IR RECEIVER (INTERNAL)	30-60Khz / $\pm 45^\circ$ / 5M
IR EMITTER (EXTERNAL)	3.5mm Stereo Phone Jack
POWER SUPPLY	DC 5V 2A
POWER CONSUMPTION	750mA (Typical) / 1000mA (Max) Without USB Power Consumption
TEMPERATURE	Operation: 0 to 55°C Storage: -20 TO 85°C Humidity: up to 95%
DIMENSIONS	4.92 x 5.51 x 1.18 in.   125 x 140 x 30 mm
WEIGHT	0.86 lbs   390g