

Smartavi DVN-8PS DVI KVMA Switch/8-Ports/USB 2.0 Up to 20 ft

Video	
Format	DVI-D Single Line
Maximum Pixel Clock	165 MHz
Input Interface (TX)	(8) DVI-D 29-pin female
Output Interface (RX)	(1) DVI-D 29-pin female
Resolution	Up to 1920 x 1200 @60Hz
DDC	5 volts p-p (TTL)
Input Equalization	Automatic
Input Cable Length	Up to 20 ft.
Output Cable Length	Up to 20 ft.
Audio	
Frequency Response	20 Hz to 20 KHz
Impedance	600 ohm
Nominal Level	0-1.0V
Common Mode	Rejection at 60dB
Input Interface	(8) 3.5mm Stereo Audio
Output Interface	(1) 3.5mm Stereo Audio
USB	
Signaling	USB 2.0, 1.1 and 1.0w/Internal Hub
Input Interface	(8) USB Type B
Output Interface	(2) USB Type A
Control	
Front Panel	Tact Switch
RS232	Via Software @ 9600 bps
IR	Via Remote Control with IR-EYE Type 3
Other	
Power	External 100-240 VAC/5VDC4A @20W
Dimensions	10.5"W x 1.875"H x 6"D
Weight	7 lbs.
Approvals	UL, CE, ROHS Compliant
Operating Temp.	0-55 °C (32-131°F)
Storage Temp.	-20-85 °C (-4-185 °F)
Humidity	Up to 95%
Emulation	NO KEYBOARD OR MOUSE EMULATION