

Smartavi MXC-HD12X16S 12X16 HDMI/RS-232/IR Expandable Matrix Switcher

| HDMI VIDEO INPUT | |
|----------------------------|---|
| Format | HDMI 1.3b [Deep Color, xvYcc color space supported] |
| DVI Compliance | Single-link DVI-D 1.1 |
| HDCP Compliance | 1.0/1.1 |
| Video Bandwidth | Single-link 340MHz [10.2Gbps] |
| Resolution | 480i,480p,720i,720p,1080i, 1080p |
| Input Interface | (1) HDMI [7.1ch audio & video] |
| Connector | Type A[19-pin female] |
| Maximum Distance | 25 ft. |
| HDMI VIDEO OUTPUT | |
| Format | HDMI 1.3b [Deep Color, xvYcc color space supported] |
| DVI Compliance | Single-link DVI-D 1.1 |
| HDCP Compliance | 1.0/1.1 |
| Video Bandwidth | Single-link 340MHz [10.2Gbps] |
| Resolution | 480i,480p,720i,720p,1080i, 1080p |
| Input Interface | (1) HDMI [7.1ch audio & video] |
| Connector | Type A[19-pin female] |
| Maximum Distance | 25 ft. |
| RCA AUDIO OUTPUT | |
| Frequency Response | 20 Hz to 20 KHz |
| Impedance | 600 ohm |
| Nominal Level | 0-1.0 V |
| Common Mode | Rejection at 60dB |
| Output Interface | Right/Left RCA Female |
| S/PDIF AUDIO OUTPUT | |
| Frequency Response | 20 Hz to 20 KHz |
| Impedance | 600 ohm |
| Nominal Level | 0-1.0 V |
| Common Mode | Rejection at 60dB |
| Output Interface | Right/Left RCA Female |
| OTHER | |
| Power | External 100-240 VAC/5VDC2A @10W |
| Dimensions | 17.125 in W x 12 in H x 12 in D |
| Weight | 20 lbs |
| Operating Temp. | 0-55 °C (32-131°F) |
| Storage Temp. | -20-85 °C (-4-185 °F) |
| Humidity | Up to 95% |