

Shinybow SB-6335T5 5 play HDBaseT PoH Extender (Transmitter) 330Ft with 2-way IR/RS-232

The SB-6335T5 HDBaseT Transmitter can transmit the HDMI, Ethernet, POH with power (48VDC), IR Remote signals input to Receiver or output to destination and the RS-232 interface signal I/O to HDBaseT Receiver (SB-6335R5 POH) via single LAN (category) cable for the long distance Maximum 328 feet (100M). Transmitter use the single UTP/FTP(category cable) CAT5e, CAT6, CAT6a or CAT7 via RJ-45 8P8C female socket(Support 568a/b). This product provide higher full HD HDMI 1.4a, Resolution supports 480i/p, 720p,1080i/p or High 4K2K quality that are identical to the source high quality full HDMI 1.4 signals. The Transmitter is useful for sending the HDMI digital Video / multi-channel audio format, IR remote in or out, Ethernet, RS-232 in, RS-232 out and POH. Controls signals via Single category cable transmit to the HDBaseT Receiver.

Inputs:

- 1x RS-232
- 1x HDMI
- 1x IR EXT. port

Outputs:

- 1x HDBaseT via CAT6/6a/7 Cable

	Distance	2-Way IR	RS-232 I/O	Power Over HDBaseT (PoH)	1x Ethernet Port (EoH)	2x Ethernet Port (EoH)	External Audio	4k2k
SB-6320T	328 feet (100m)	Yes	Yes			Yes	Yes	
SB-6320R	328 feet (100m)	Yes	Yes			Yes	Yes	
SB-6333T / R KIT	230 feet (70m)	Yes	Yes					Yes
SB-6333T3 / R3 KIT	328 feet (100m)	Yes	Yes					Yes
SB-6335T / R KIT	328 feet (100m)	Yes	Yes					Yes
SB-6335T4	328 feet (100m)	Yes	Yes		Yes			Yes
SB-6335R4	328 feet (100m)	Yes	Yes		Yes			Yes
SB-6335T5	328 feet (100m)	Yes	Yes	Yes	Yes			Yes
SB-6335R5	328 feet (100m)	Yes	Yes	Yes	Yes			Yes

FEATURES

- HDBaseT Transmitter Extend the HDMI signal over single category cable.
- Transmit signals are HDMI, IR in/out, Ethernet, RS-232 I/O and POH(Power Over HDBaseT).
- Category cable via using the CAT6, CAT6a and CAT7 (UTP or FTP) cable for 568a or 568b.
- HDBaseT link speeds of up to 3.4 Gbps, HDMI 1.4, full HD 4K2K signal, HDCP compliant.
- Support Digital RGB 36bits, HDMI digital video TMDS, digital multi-channel audio format.
- Extension higher quality full HD DVI video WUXGA 1920x1200 resolution.
- Support High Defi nition worldwire range resolution 480p, 720p 1080i/1080p-60Hz and 4K2K.
- Extend long distance 328 feet (100M) between HDBaseT Transmitter and Receiver.
- Support wall mount and rack mount install total 13 pcs into one 19 inch 4U Rack mountable.
- Power input via DC with Low power consumes (Full load 750mA)
- Power supply using universal power switch 50/60Hz,100~240VAC