

Shinybow SB-6335T5 5 play HDBaseT PoH Extender (Transmitter) 330Ft with 2-way IR/RS-232

- Type of Extender: HDBaseT Transmitter transmit the HDMI signal over single category cable
- Input Signals: HDMI with Digital Video (TMDS)/Audio .5~1.0vPP, DDC5Vpp
- HDBaseT Supports: HDMI 1.4 Standard, DVI and HDCP Compliant
- Video Support: HDMI and DVI TMDS format for 1920x1200 resolution up to 3.4 Gbps Digital RGB 36bits deep color, 3D 1.4a HDMI format
- Audio I/O Supports: Multi-channel Audio Formats 5.1 / 7.1, MAT(MLP), Dolby Digital, Dolby TrueHD, Dolby Digital Plus, DTS, DTS-ES 6.1, DTS-HD, DTS-HD-HRA, DTS-HD Master, (PCM-2CH)
- PoH Distance: With power over HDBaseT
- Cable Support: CAT6, CAT6a, CAT7 use UTP or FTP category cable
- Support HDMI Resolution: 480p, 720p 1080i/1080p@60Hz or 4K2K@24Hz
- Scan Rate Accepted: Support HDMI full HD Resolutions; Frequency 24Hz to 60Hz
- Control: 1x IR in, 1x IR out, 1x RS-232 I/O and 1x Ethernet series interface
- IR Infrared Frequency: 38Khz
- Extend Distance: Up to 328 feet (100 meters) via (UTP or FTP CAT6 100m cable)
- Extend Distance: Up to 100M (CAT6)
- Safety Approvals: CE, FCC, VCCI, REACH & WEEE
- Dimensions (LxWxH): 5.12 x 5.12 x 1.14 in (130mm x 130mm x 29mm)
- Rack Mount: Total 13 pcs install into 19 inch 4U Rack mountable
- Shipping Weight: 0.385 kgs / 0.847 lb
- Power Consumption: Max. 750mA. (Full load 1080p-60Hz signal with use DC12V input)
- Power Supply: Extra Power Input +48VDC, 1A. (Universal Type 50/60Hz, 100~240 VAC)