

Aten PE8108A Power Distribution Unit

Power Outlets	Direct: 8
Connectors	Power Inlets: 1 x IEC 320 C20 Power Outlets: 8 x NEMA 5-15R Sensor: 2 x RJ-11, female LAN: 1 x RJ-45, female
LEDs	Outlet Status: 8 (orange) Outlet / IP: 1-digit 7-segment (orange) PDU Current / Outlet Current / IP: 3 (green) Current / IP: 3-digit 7-segment (orange) Power: 1 (blue) 10/100 Mbps: 1 (orange / green) Link: 1 (green) Sensor: 2 (green)
Switches	Reset: 1 x Semi-recessed pushbutton Power: 1 x Non-fuse Breaker Select: 1 x pushbutton
I/P Rating	100 to 120V~; 50 to 60 Hz; 14 A (UL), 20 A (Max.)
Load Capacity	1440 W
O/P Rating	Per Port: 100 to 120 V~: 50 to 60 Hz; 12 A Total: 100 to 120 V~: 50 to 60 Hz; 12 A
Environment	Operating Temperature: 32 to 122°F (0 to 50°C) Storage Temperature: -4 to 140°F (-20 to 60°C) Humidity: 0 to 80% RH Non-condensing
Physical Properties	Power Cord Length: 9.8' (3 m) Housing: Metal Dimensions (L x W x H): 17.02 x 8.63 x 1.73" (43.24 x 21.93 x 4.40 cm) Weight: 6.17 lb (2.8 kg)