

Kramer MV-5 5-Channel DVI/SDI/RGB/Component Multiviewer

INPUTS

- 4 RGB/component HD on 20 BNC connectors, 6 analog SD on 12 BNC connectors, 5 DVI-D on DVI-I connectors, 4 SDI on BNC connectors

OUTPUTS

- 1 RGB/component HD on 5 BNC connectors, 1 DVI-D on a DVI-I connector, 2 SDI on BNC connectors

MAXIMUM OUTPUT LEVEL

- 800mVpp/75Ω

JITTER

- Better than 0.2UI

DATA RATE

- Up to 2.97Gbps

HDMI BANDWIDTH

- Up to 6.75Gbps data rate (2.25Gbps per graphic channel)

COMPLIANCE WITH HDMI STANDARD

- HDCP (DVI inputs/outputs)

SUPPORTED OUTPUT RESOLUTIONS

- **640x** 48 48 48 48
- **800x** 60 60 60 60
- **1024x** 76 76 76 76
- **1152x** 86
- **1280x** 76 76 76 76 96 76 10 10
- **1360x** 76
- **1366x** 76
- **1400x** 10 10 10
- **1440x** 90 90 90 90
- **1600x** 12
- **1680x** 10 10
- **1920x** 12

POWER CONSUMPTION

- 100-240V AC, 50/60Hz, 57VA

CONTROLS

- Front panel buttons, RS-232, Ethernet

OPERATING TEMPERATURE

- 0° to +40°C (32° to 104°F)

STORAGE TEMPERATURE

- -40°C to +70°C (-40° to 158°F)

HUMIDITY

- 10% to 90%, RHL non-condensing

INCLUDED ACCESSORIES

- Power cord, rack "ears"

PRODUCT DIMENSION

- 19" x 9.29 x 2U (43.6cm x 23.60cm 8.80cm) W, D, H

PRODUCT WEIGHT

- 3.7kg (8.0lbs) approx

SHIPPING DIMENSION

- 55.00cm x 34.00cm x 15.50cm (21.65" x 13.39" x 6.10") W, D, H

SHIPPING WEIGHT

- 4.9kg (10.8lbs) approx