

# Kramer VP-733 12-Input ProScale Presentation Matrix Switch/4K30 UHD Scaler with Preview and Program Outputs and Legacy

## INPUTS

- 4 HDMI: On female HDMI connectors
- 4 Universal: On 15-pin D-sub connectors
- 2 Display Port: On female Display Port connectors
- 2 HDBaseT: On RJ-45 connectors
- 10 Unbalanced Stereo: On 3.5mm mini jacks
- 1 S/PDIF: On an RCA connector

## OUTPUTS

- 2 HDMI: On female HDMI connectors
- 1 Display Port: On a female Display Port connector
- 1 HDBaseT: On an RJ-45 connector
- VGA/HD: On a 15-pin D-sub connector
- 1 S/PDIF: On an RCA connector
- Balanced Audio (Speaker): On a 5-pin terminal block connector

## ACCESSORIES

- Included: IR remote control, power cord, rack ears

## PORTS

- RS-232: On a 9-pin D-sub connector
- Ethernet: On an RJ-45 connector

## VIDEO

- HDMI Standards Compliance: Supports HDMI and HDCP

## USER INTERFACE

- Controls: Front panel buttons/OSD, IR remote control, RS-232 on a 9-pin D-sub connector, Ethernet
- Additional Controls: Picture-In-Picture, Picture-and-Picture or Split Screen (two images side-by-side)
- Additional Controls: Separate program/preview freeze and zoom, different selectable vertical refresh rates, Video and Audio ProcAmp control, output image scaling and aspect ratio change, EDID capture

## POWER

- Input: 100-240V/50-60Hz
- Consumption: 700mA

## ENVIRONMENTAL CONDITIONS

- Operating Temperature: 0° to +40°C (32° to 104°F)
- Storage Temperature: -40° to +70°C (-40° to 158°F)
- Humidity: 10% to 90%, RHL non-condensing

## PRODUCT DIMENSION

- 19" x 9.34 x 1U (43.6cm x 23.72cm 4.36cm) W, D, H

## SHIPPING DIMENSION

- 52.50cm x 33.00cm x 10.70cm (20.67" x 12.99" x 4.21" ) W, D, H