

Matrox XTO2EX-F2408F Extio F2408E Expander

Part numbers	- Matrox Extio F2408 unit: XTO2-F2408F <i>The following items are sold separately:</i> - PCIe interface card: XTO2A-FESLPAF - Single mode upgrade kit: XTO2-2SMTXF - Matrox Extio F2408E Expander unit: XTO2EX- F2408F
Graphics memory	1 GB
PCIe interface card	PCI Express x1 card
EMC certifications	Class A: ACMA, CE, FCC, VCCI
Laser emissions	850 um laser compliant to 21CFR, Subpart J, Class 1
Maximum distances	OS1, OS2 single-mode 9/125 μm (1 km / 3280 feet) OM1 multi-mode 62.5/125 μm (70 meters / 230 feet) OM2 multi-mode 50/125 μm (150 meters / 492 feet) OM3 multi-mode 50/125 μm (380 meters / 1247 feet) OM4 multi-mode 50/125 μm (400 meters / 1312 feet)
Extio F2408 unit size	29.97 cm x 2.92 cm x 14.73 cm / 11.8" x 1.15" x 5.8" (width x height x depth)
PCIe interface card size	16.76 cm x 6.8 cm x 1.91 cm / 6.6" x 2.677"x 0.75"
Warranty	2 years