

SWIT FM-21HDR 21.5-inch High Bright HDR Production LCD Monitor

LCD Performance		
Size	21.5 inches	
Display area	476.64x268.11mm	
Resolution	1920x1080	
Aspect ratio	16:9	
Brightness	1000cd/m2	
Contrast	1000:1	
Color	16.77 million colors	
Viewing Angle	Horizontal: 178° Vertical: 178°	
Input		
BNC x2	3G/HD/SD-SDI input	
BNC x1	CVBS input	
HDMI x1	HDMI 1.3 input	
3.5mm x1	Analog audio input	
USB x1	User LUTs upload and Firmware upgrade	
RS485 x1	TSL 3.1/4.0 input	
Output		
BNC x1	3G/HD/SD-SDI loop output	
RS485 x1	TSL 3.1/4.0 output	
3.5mm x1	SDI, HDMI embedded audio and analog output	
Video Format		
SDI	SMPTE-260M	1035i (60 / 59.94)
	SMPTE-425M	1080p (60/59.94/50)
		1080i (60/59.94/50)
	SMPTE-274M	1080p (30/29.97/25/24/23.98)
		1080i (60/59.94/50)
	SMPTE-RP211	1080psf (30/29.97/25/24/23.98)
	SMPTE-296M	720p (60/59.94/50)
SMPTE-125M	480i (59.94)	
ITU-R BT.656	576i (50)	
HDMI	480i/ 576i / 480p / 576p	
	1080i (60 / 59.94 / 50)	
	720p (60 / 59.94 / 50)	
	1080p (60 / 59.94 / 50 / 30 / 29.97 / 25 / 24 / 23.98)	
General		
Input voltage	DC / battery 11V-17V 3A, AC 100-240V, 50/60Hz	
Power consumption	48W	
Working temperature	0°C■+50°C	
Working humidity	10%■90%	
Storage temperature	-15°C■+60°C	
Storage humidity	10%■90%	
Dimensions	517x319x74.3mm	
Net weight (w/o stand)	5.7kg	