

Apantac HDBT-SET-5-II HDBaseT HDMI Extender (Transmitter/Receiver) Kit with PoE/VGA Input/330ft

MODEL	HDBT-1-EAPv-II	HDBT-1-RAP
DESCRIPTION	Switchable VGA w/Audio) or HDMI HDBaseT Extender with IR, RS232"	Single-port HDBaseT HDMI Receiver with IR, RS232, GPI and assignable POE
INPUTS	1 x HDMI 1 x VGA with analog audio 1x RS232 lxIR (3.5 mm Jack) 1 x Terminal Block for switch	1 x RJ45 (Link) 1 x Direct IR Receiver (On Top) 1 x Extended IR Receiver (3.5 mm Jack)
OUTPUTS	1 x RJ45 (Link) 1 x HDMI Loop out 1 x IR Out (3.5 mm Jack for Emitter)	1 x HDMI 1x RS232 1 x Terminal Block for GPI Out
RESOLUTION	Maximum Resolution of UHD @ 60Hz (4:2:0) / 1920 x 1200 (including 1080P and 3D) up to 330 feet (100 meters)	
DIMENSIONS	140 mm W x 114 mm D x 37.5 mm H	122 mm W x 74 mm D x 38 mm H
POWER	DC 48 V	POE