

Altinex TP115-402 HDMI over IP Receiver/HDCP Compliant

Features/Description	TP115-402
Input Connectors	
IP	RJ45 F, Shielded (1)
DC Power	2.5 mm center pin (1)
Output Connectors	
HDMI	HDMI F, Type A (1)
Audio (Analog)	3.5 mm stereo (1)
Balanced Analog Audio	5-pin terminal block (1)
Control	
IRRX	3.5 mm F (1)
RS232	3.5 mm F (1)
Factory Reset	Push Button
Compatibility	
Signal types	HDMI, audio
Video Signal resolutions	480p/720p/1080i/1080p
Streaming Bit Rate	
IR Frequency	Support 38 k-56 kHz
RS232 Baud rate	Default 2400 bps
Accessories Included	
Power supply	+12V, 2AUS, EU, AU, UK plugable blades
IR RX	
Connector	5-pin plug for RS-232 cable termination (1)
Mounting hardware	2 brackets, 8 screws
Mechanical	TP 115-402
Material	Aluminum
Color	Black
Height	1 in (25 mm)
Width	5.3 in (135 mm)
Depth	3.1 in (79 mm)
Weight	0.35 lb. (0.16 kg)
T° Operating	10°C-45°C
Humidity	90% non-condensing
MTBF (calc.)	38,000 hrs.
Electrical	TP115-402
Video Input Signals	
Digital Video + Audio	HDMI over IP
Video Output Signals	
Video	HDMI Standard
Audio Output Signals	
Analog Audio	Line Level
Balanced Analog Audio	Line Level
Power	
12 V	0.35 A
Total Power	4.2 W