

TVlogic F-7H mk2 7 inch FHD 3G-SDI/HDMI 1.4 HDR Field Monitor with Max Luminance 3600 nit

LCD	Size	7"
	Resolution	1920x1080(16:9)
	Pixel Pitch	0.079(W) x 0.076(H) mm
	Color Depth	16.7M (True)
	Viewing Angle	H : 160 degrees/V: 160degrees
	Luminance of white	3600 cd/ m2 (Max.)
	Contrast Ratio	1,200:1
	Display Area	151.2(H)x94.5(V) mm
Input	1 X HDMI	HDMI Input 1Ch
	1 X BNC	3G/HD/SD SDI Input 1Ch
Output	1 X HDMI	HDMI Output 1Ch
	1 X BNC	3G/HD/SD SDI Output 1Ch
Input Signal	3G-SDI	2.970Gbps
	HD-SDI	1.485Gbps
	SD-SDI	270 Mbps
	HDMI	480i / 480p / 576i / 576p / 720p / 1080i / 1080p
SDI Input Signal Formats	SMPTE-425M-A/B	1080p(60/59.94/50/30/29.97/25/24/23.98/30sF/29.97sF/25sF/24sF/23.98sF) 1080i(60/59.94/50)
	SMPTE-274M	1080i (60/59.94/50)
		1080p (30/29.97/25/24/24sF/23.98/23.98sF)
	SMPTE-296M	720p (60/59.94/50)
	SMPTE-125M	480i (59.94)
ITU-R BT.656	576i (50)	
Audio In	SDI Embedded Audio (Group, Ch Selectable)	
Audio Out	External Output Port (3.5m Phone Jack)	
Power	DC 12V 1.8A	
Power Consumption (Approx.)	19W	
Tally Signal In/Out Level	DC5V±2V	
Operating Temperature	0°C to 40°C (32°F to 104°F)	
Storage Temperature	-20°C to 60°C (-4°F to 140°F)	
Main Body Dimensions (mm/inch)	211 X 125 X 28.3 (8.3 X 4.95 X 1.11)	
Box Dimensions (mm/inch)	290 X 158 X 83 (11.42 X 6.22 X 3.27)	
Weight	0.76Kg/1.68 lbs	
Basic Accessories	BNC Connector, Camera Mount, D-Tap cable	
Optional Accessories	Tripod Ball Head, Camera Mount, Battery Bracket, V-mount, G-Mount, HDMI Bracket, Carrying Case	