LTS CMIP9863W-SZ 6MP Platinum Varifocal Motorized Bullet Network IP Camera/2.8-12mm Lens/IP67/IK10

Camera	
Image Sensor	1/2.9" Progressive Scan CMOS
Min. Illumination	Color: 0.01 8 Lux @(F 1.6, AG CON)
Shutter Speed	1/3 s to 1/100,000 s
Slow Shutter	Support
Lens	2.8-12mm @F1.6, Motorized Lens, Angle of viewï¼š88° to 27°
Lens Mount	Φ14
Day & Night	IR cut filter
DNR	3D DNR
Wide Dynamic Range	120dB
3 Axis Adjustment	Pan:0° - 355°, Tilt: 0° - 90°, Rotation: 0° - 355°
Compression Standard	
Video Compression	Main stream: H.265+/H.265/H.264 Zip+/H.264 Sub stream: H.265+/H.265/H.264 Zip+/H.264/MJPEG Third stream: H.265+/H.265/H.264 Zip+/H.264
H.264/H.264+	Main Profile / High Profile
H.265/H.265+	Main Profile / Main Stream Support
Video Bit Rate	32 Kbps to 16 Mbps
Audio Compression	G722.1/G711ulaw/G711alaw/G726/MP2L2
Audio Bit Rate	64Kbps(G.711)/16Kbps(G.722.1)/16Kbps(G.726)/32-192Kbps(MP2L2)
Image	
Max. Resolution	3072 × 2048
Frame Rate	50Hz: 20 fps (2944× 1656), 25 fps (2560 × 1440, 1920 × 1080, 1280 ×720) 60Hz: 20 fps (2944×1656), 30 fps (2560 × 1440, 1920 × 1080, 1280 ×720)
Sub Stream	50Hz: 25fps (640 × 480, 640 × 360, 320 × 240) 60Hz: 30fps (640 × 480, 640 × 360, 320 × 240)
Third Stream	50Hz: 25fps (1280 ×720, 640 × 360, 352 × 288) 60Hz: 30fps (1280 ×720, 640 × 360, 352 × 240)
Image Setting	Rotate mode, saturation, brightness, contrast, sharpness adjustable by client software or web browser
Network	
Network Storage	Support Micro SD/SDHC/SDXC card (128G), local storage and NAS (NFS,SMB/CIFS), ANR
Alarm Trigger	Motion detection, video tampering, network disconnected, IP address conflict, illegal login, HDD full, HDD error, Alarm input, Alarm output
Protocols	TCP/IP, UDP, ICMP, HTTP, HTTPS, FTP, DHCP, DNS, DDNS, RTP, RTSP, RTCP, PPPoE, NTP, UPnP, SMTP, SNMP, IGMP, 802.1X, QoS, IPv6, Bonjour
General	One-key reset, anti-flicker, three streams, heartbeat, password protection, privacy mask, watermark, IP address filter
Standard	ONVIF (PROFILE S, PROFILE G), PSIA, CGI, ISAPI
Interface	
Communication Interface	1 RJ45 10M/100M self-adaptive Ethernet port
Reset	Yes
General	
Working Temperature /Humidity	-22 °F ~ 140°F (-30 °C ~ 60 °C) Humidity 95% or less (non-condensing)
Power Supply	DC12V ± 25%, PoE (802.3af)
IR Range	Up to 165ft (50m)

Weather Proof Ratings	IP67
Impact Protection	IK10
Dimensions	Φ 5 .7” × 13.1”(Φ 144.13 × 332.73 mm)
Weight	4.2 lbs (1893 g)