

LTS LTK3500S Video Access Control Terminal and Doorbell

Properties	
Processor	3.2 Bit high-performance Processor
Camera	2MP/1920x1080, IR Light
Audio	Audio Input: Built-in Microphone (Sensitivity: -25±3dB); Audio Output: Built-in Loudspeaker (1W)
Card Capability	50,000
Record Capability	200,000
SD Card	Supported
Card Reading Mod	Mifare/CPU Serial No.
Card Reading Distance	>=20mm
Communication Mode	Terminal Mode: Uplink(TCP/IP), Downlink(RS485); Card Reader Mode: Uplink(Wiegand26/34, RS-485)
Input Interface	1x Doorbell Button, 1x Door Magnetic Sensor, 2x Alarm Input, 1x Tamper-Proof Switch, 1x Exit Button
Output Interface	1x Lock, 1x Alarm Output (Doorbell)
Video Storage	Record and save video through NVR
SD Card	Supported
Protection Level	IP65
Power Supply	DC 12V/1A
Working Current	600mA (max)
Working Temperature	-4°F to +149°F(-20°C to +65°C)
Working Humidity	10 % to 90 % (Non-Condensing)
Faceplate Material	Brushed Metal
Dimensions	8.58"x3.07"x"(218mmx78mmx41mm)
Mounting	Surface Mounting, Metal Door Mounting