

## Hall Research HHD264-R HDMI over LAN Receiver

- **Protocol:** H.264 encoding
- **Input Resolution:** VGA or 480p to Full HD 1080P@60 640x480@60, 800x600@60, 1024x768@60, 1280x1024@60 1440x900@60, 1680x1050@60, 1360x768@60, 1366x768@60, 1400x1050@60, 1680x1050@60, 1920x1080@60
- **Input Ports:** 1x RJ45 / 1x IR
- **Output Ports:** 1x HDMI
- **RS232 Port:** TX 1x DB9 Female / RX 1x DB9 Male
- **Baud Rate:** Bidirectional, pass thru 2400 - 115200 bps
- **Audio:** HDMI Stereo 2-channel
- **IR Frequency:** 38-56 KHZ pass-thru modulated
- **Group ID:** Up to 64 groups
- **Switch/Router:** Gigabit IGMP and DHCP support
- **Operating Temp:** +23 to +95F (-5 to +35°C)
- **Power Consumption:** Max. 3 W
- **Mounting Option:** Mounting Brackets (included)
- **Dimensions:** 4.72"(120.2mm) W x 3.09"(78.6mm) D x 1.14"(29 mm) H
- **Net Weight:** TX: 0.28KG / RX:0.28KG