

## Soundtube RS31-EZ-T 3 inch On-Ceiling Speaker/20W Transformer

System Type	3" Full range, open ceiling, sealed (20 Watt optional transformer for 25/70.7/100 Volt or voice coil direct)
Nominal Impedance	8 ohm
Impedance (minimum)	8.0 ohm
Sensitivity dB @ 2.83V/1M	85.0dB
Sensitivity dB @ 1W/1M (2)	85.0dB
Frequency Response ( $\pm 3$ dB)	170 Hz - 14 kHz
Frequency Response ( $\pm 10$ dB)	120 Hz - 22 kHz
Max. Program Power	40w
Max. Continuous Power RMS	20w
Max. Power SPL @ 1 M	98.0dB
Tap Selector	Selectable terminal input strip
70.7 Volt Transformer Taps	20w / 98.0dB
100 Volt Transformer Taps (dB)	20w / 98.0dB
25 Volt Transformer Taps (dB)	3w / 90.0dB
Transformer Options	25 / 70.7 / 100 Volt option, no 8 ohm bypass
Colors	Black or white
Woofer - part	76.1 mm (3.0 in.) Polypropylene driver w/ butyl rubber surround.
Inputs	Terminal strip
Height (SM = Height)	125.4 mm / 4.93 in
Diameter (SM = Width)	110.5 mm / 4.35 in
SM Depth (Including Bracket)	96.8 mm / 3.81 in
Weight	0.6 kg / 1.32 lb
Shipping Weight	0.9 kg / 1.98 lb
Packaging	1 per box
Regulatory - UL	1480 planned
Regulatory - CE	Approved
Regulatory - RoHS	approved
Regulatory - IP	not planned
Regulatory - CCC	approved