

AG Neovo PS-55 55in SEMI RUGGED VGA/DVI/HDMI/CVBS/YPbPr/DP LCD DISPLAY/AIP/OPS

Built on an LED-backlit panel with the capacity of 700 nits high brightness, the PS-55 reproduces life-like colours and image details without disturbance of ambient light. Designed to suit different environments, it can be displayed either landscape or portrait. Equipped with an OPS slot and RJ45/RS-232 remote control functions, the PS-55 is an ideal choice for easy media integration and maintenance. The Anti-Burn-in™ technology and HeatControl Sensor ensure the 24/7 round-the-clock performance in professional digital signage settings.

Features

- LED-backlit technology with FHD 1920 x 1080 resolution
- 700 nits high brightness
- Premium-grade panel for high reliability and long product lifetime
- Anti-Burn-in™ technology
- AIP technology: 3D Comb Filter/ Deinterlace/ Noise Reduction/PIP and PBP
- EcoSmart Sensor detects ambient lighting condition and automatically adjusts brightness level to reduce power consumption
- Versatile connectivity: VGA, DVI, HDMI, CVBS, YPbPr, DisplayPort
- Daisy chain availability: VGA, DVI, RS-232
- RS-232 and RJ45 allow programmable remote control
- 15.8 mm bezel width and tiling function for easy video wall setup (support up to 5 x 5)
- Built-in scheduler allows different programme scheduling
- HeatControl Sensor automatically activates the internal cooling fan to cool down the temperature
- OPS slot ready for easy media player integration
- Built-in speakers
- Quick switch between internal and external speakers
- Flexible display orientation: portrait and landscape
- Rigorous screening of the components for mission-critical 24/7 applications