Gefen EXT-DPKVM-422 2x2 KVM switch for DisplayPort, USB and Audio

Switches two high-definition displays between two DisplayPort-equipped computers with audio/video and USB peripherals

Switch between two computers (each using two graphic DisplayPort outputs) effortlessly, using the Gefen 2x2 DPKVM Switch. With the output utilizing two displays and two USB 2.0 ports, users can switch audio, video and USB for each computer. Access two computers from one workstation without having to use a network. Switch through the front panel "select" button, using the supplied IR remote control, the RS-232 serial port, or the IP control. The 2x2 DPKVM Switch is compatible with all operating systems using DisplayPort and USB.

How It Works

Connect two DisplayPort high-definition displays, USB 2.0 keyboard/mouse, or other USB 2.0 peripherals to the 2x2 DisplayPort KVM Switch output. Connect the DisplayPort, USB and audio ports on both computers to the 2x2 DPKVM Switch input using the supplied cables.

Note: If the source and/or display is not 100% DisplayPort compliant, a protocol-specific protocol adapter will be required in order to connect the source to the Switcher and/or the Switcher to a high-resolution display.

Features:

- Switches two high-definition displays between two DisplayPort-equipped computers with audio/video and USB peripherals
- Switches up to 2560 x 1600 resolution
- Supports RGB and YCbCr color spaces
- Rack mountable
- Save space on your desktop

Specifications:

- Input Connector: (4) DisplayPort (from computers)
- Output Connector: (2) DisplayPort (to display)
- Input Connector: (2) USB 2.0 Type "B" (from computers)
- Output Connector: (2) USB 2.0 Type "A" (to keyboard/mouse)
- Input Connector: (2) 3.5mm analog L/R audio (from computers)
- Output Connector: (1) 3.5mm analog L/R audio (to speakers or amplifier)
- Color Spaces: RGB and YCbCr
- Maximum Resolution: 2560x1600
- Dimensions: 8.41"W x 1.57"H x 4.23"D

Package Includes:

- (1) 2x2 DPKVM Switch DisplayPort USB Audio Switcher
- (4) 6-foot DisplayPort cables
- (2) 6-foot USB 2.0 cables
- (2) 6-foot 3.5mm mini-stereo audio cables
- (1) 5V DC Universal Power Supply (Locking Type)
- (1) IR Remote Control (RMT-2IR)
- (1) RS-232 Serial Cable
- (1) Rack ears
- (1) User's Manual