

Soundtube LA808i-CP Extended Low Frequency Directivity/4 Ohm/Custom Paint

This listing is for LA808i-Custom Paint - Custom Paint

NOT a subwoofer, the SoundTube LA808i is designed to increase the directivity of low frequencies in SoundTube's Line Array system. It can be used only in conjunction with the LA880i 3-way line array. The use of the LA808i is recommended in spaces that have a large reverberation time. When a single unit is added to the LA880i, directivity of low frequencies is increased by up to an octave lower than with the LA880i alone. The product's dimensions are identical to those of the LA880i. The LA808i must be placed either directly above or directly below the LA880i in order for the system to work properly. If desired, two LA808i units can be added: one above the LA880i and one below.

Features

- Passive, fixed length, low frequency directivity element for SoundTube Line Array.
- Designed for use only with LA880i Line Array.
- Eight 4.5 inch (115 mm) woofers.
- Extends low frequency directivity of line array systems by up to an octave lower than with the LA880i alone.
- Paintable enclosure is constructed of MDF and plywood with metal threaded mounting points.
- Powder coated, paintable steel grille.
- Available in black or white paint finish.
- Custom woodgrain cabinets or paint finishes available (contact us for details).
- Flexible mounting options include surface-mount, pole-mount, ceiling-mount or suspended (flown). (Allen Products mounting accessories sold separately.)
- Euroblock and SpeakOn connectors allow for fast connections and easy daisy chaining.
- UL 1480 UEAY planned.
- Included accessories: safety cable mounting plate and mounting bolts, Euroblock connector, safety cable.
- NOTE: Mounting brackets not included