

Gefen EXT-DVI-FM500-150B DVI Extender Over Two Strand Fiber Link + Edid (150ft Kit)

Painless, reliable DVI extension over fiber -- with built-in DVI-to-fiber signal converters and EDID storage, all in a tiny form factor!

The DVI-FM500 Extender lets you extend your DVI source up to 5,000 feet away using a 100% fiber optic extension solution. Attractive and compact DVI-to-fiber modules connect to each other via just two LC fiber optic cable strands. Extender units fit neatly behind equipment for a clean installation.

The on the fly EDID programming feature enables quick and correct synchronization of the video resolution to the display without any manual configuration. It's a great way to extend DVI easily and cleanly.

How It Works

The DVI FM 500 Sender unit plugs into a DVI port (either a computer source or another device transmitting a DVI signal). The DVI FM 500 Receiver unit plugs into a DVI display - up to 5,000 feet away. Two-strand LC fiber optic cable connects the DVI FM 500 Sender unit and the DVI FM 500 Receiver units to each other. Power is connected to the DVI FM 500 receiver using the 5V wall adapter and a crisp, vibrant HD picture appears on the display.

Optical signal transmission provides immunity from electromagnetic interference (EMI).

Note:

The distance that DVI can be extended will depend on the type of fiber optic cable used.

For a maximum resolution of 1920x1200 at 60 frames per second (60 Hz), the distances possible are as follows:

Single mode: 9(8)/125 micron core: 1500m (5,000 ft)

Multi mode: 50(62.5)/125 micron core: 500m (1,500 ft)

An external +5VDC power adapter is generally required for the receiver module. Most video cards can provide +5V DC power to the transmitter module but it also has provision for external power. Both power supplies are included.

This device is not HDCP compliant

Features:

- Extends resolutions up to WUXGA (1920x1200) @60 Hz up to 5,000 feet away
- Immune to EMI (electromagnetic interference) thanks to all-fiber signal transmission media
- Automatic EDID Programming feature enables quick and correct sync of source to display
- Compact Sender and Receiver units install in minutes
- Supports both singlemode and multimode fiber optic cable types
- Fully Supports DVI 1.0 and DDC2B via virtual DDC

Specifications:

- Video Amplifier Bandwidth: 165 MHz
- Maximum Single Link Resolution: WUXGA (1920x1200)
- Default EDID: UXGA (1600x1200)
- Video Input (Sender): DVI-D SL 24-Pin Female
- Video Output (Receiver): DVI-D SL 24-Pin Female
- Fiber Link Connectors (Sender/Receiver): Dual LC-LC SM/MM (each)
- LED Indicators (Sender/Receiver): (1) EDID Status
- Program Button (Sender): EDID Program (recessed)
- Power Supply: 5V DC (Required for Receiver; Optional for Sender)
- Power Consumption: 2.2 Watts (Typical, Each)
- Operating Temperature: 0°C - 50°C
- Storage Temperature: -10°C - 85°C
- Operating Humidity: 5% - 85%
- Dimensions: 1.5" W x 0.6" H x 2.7 " D
- Shipping Weight: 1 lb.

Package Includes:

- (1) DVI FM 500 Sender unit
- (1) DVI FM 500 Receiver unit
- (2) 5V DC Power Supply
- (1) User's Manual

- (1) 2 x LC 150 ft fiber cable