Soundtube RS4-EZ 4 inch Full-Range Open-Ceiling Speaker

One 4 inch (102 mm) full-range, treated fiber driver mounted to an ABS baffle. Includes hanging hardware with galvanized steel cables and integrated SpeedClamp[™] self-locking wire grip for fast, easy and secure installation. Also includes Euroblock connector and terminal weather boot. Patented ZeroReflection[™] enclosure technology for optimal sound reproduction and cabinet rigidity. Easy access five-position selectable tap switch for 25-, 70.7- and 100-volt applications with transformer bypass position simplifies ordering and inventory tracking. Steel grille with protective powder-coated finish for lasting durability. Average sensitivity of 90.0 dB offers high-output capabilities and reduced amplification costs. UL 2239 (hanging cable) listed.

Features:

- One 4 inch (102 mm) full-range, treated fiber driver mounted to an ABS baffle.
- Weatherized components for indoor and outdoor applications.
- Includes hanging hardware with galvanized steel cables and integrated SpeedClamp[™] self-locking wire grip for fast, easy and secure installation. Also includes Euroblock connector and terminal weather boot.
- Patented ZeroReflection[™] enclosure technology for optimal sound reproduction and cabinet rigidity.
- Easy access five-position selectable tap switch for 25-, 70.7- and 100-volt applications with transformer bypass position simplifies ordering and inventory tracking.
- Steel grille with protective powdercoated finish for lasting durability.
- Average sensitivity of 90.0 dB offers high-output capabilities and reduced amplification costs.
- UL 2239 (hanging cable) approved
- High-quality black or white paint finish. Custom colors available.
- Optional accessory: AC-RS-SM5 bracket for surfacemount applications.