

Kramer NT-52P 2-Port Universal I/O PoE Control Gateway

The NT-52P is a compact universal-I/O PoE control gateway, capable of plug and play deployment over customer Ethernet LAN for remote control of customer-controlled devices via two universal I/O ports. The ports can be configured as bidirectional RS-232, crossed RS-232, RS-485, IR, GPI/O or relay control connections. Multiple control clients can be IP-connected to the NT-52P control gateway for concurrent control of devices, such as AV scalers, video projectors and displays, audio amplifiers, DVD players, sensors, screens, shades, door locks, and lighting.

Features:

- **Innovative Universal I/O Ports** — Remote IP-based control of any device connected to the control gateway universal I/O ports, with selectable port configuration to bidirectional RS-232, RS-232 cross, RS-485, IR, GPI/O or relay control. Each port is adaptable for any room device control simply by toggling a button.
- **Multiple IP Connected Clients** — Remotely connected over customer Ethernet network, concurrently controlling any devices connected to control gateway universal I/O ports.
- **Easy & Reliable Installation** — With single PoE cable for both, powering and connectivity, and Plug and Play IP installation with dynamic (DHCP) address resolution and auto device discovery over customer LAN. Highly-resilient powering with multiple power options — USB, Power over Ethernet per IEEE 802.3af standard, and optional PSU (not included). Compact, designed for piggy-back installation, such as behind a TV or display, with the ability to draw power from device USB port and Ethernet connectivity.
- **Remote Management** — Built-in web UI for remote browser-based management and support, by multiple IP-clients over customer LAN. Easy firmware upgrades, either remotely via customer LAN, or locally via device USB port.