# Gefen EXT-DVI-142SL 1:2 DVI SL Splitter (Discontinued. Replaced by EXT-DVI-142DL)

## GEFEN 1X2 DVI SINGLE LINK SPLITTER. MODEL: EXT-DVI-142SL

### Allows computers with DVI output to be connected to two or more DVI displays.

The 1x2 DVI SL Splitter allows computers with DVI output to be connected to two or more DVI displays at the same time. It is a flexible distribution hub that can accommodate multiple displays when two or more 1x2 DVI SL Splitter are connected together to create a greater distribution.

#### How it works

The 1x2 DVI SL Splitter is connected with a DVI cable from the DVI source to the 1x2 DVI SL Splitter input. There are two DVI outputs. DVI output 1 is the primary connection and is used for the main display. DVI output 2 follows the main display.

### Note: Only output 1 of the 1x2 DVI SL Splitter is HDCP pass-through.

Please use The HDMI Splitter if you require two HDCP compliant outputs.

### Package Includes:

- the Mini DVI Hub
- One 5v Power Supply
- One 6ft DVI cable

### Features:

- Splits the DVI signal to two or more displays
- Connects two or more displays at the same time to the same video source
- Uses high quality DVI cables for connections
- Allows simultaneous display
- Supports resolutions up to 1080p, 2K, and 1920  $\times$  1200
- Supports HDCP passthrough for output one
- Supports DDWG standard for DVI compliant monitors

# Specifications:

- Video Amplifier Bandwidth: 1.65 Gbps
- Input Video Signal: 1.2 volts p-p
- Input DDC Signal: 5 volts p-p (TTL)
- Single Link Range: 1080p/1920 x 1200
- DVI Connector: DVI-I 29 pin female (digital only)
- Power Consumption: 15 watts (max.)
- Power Supply: 5V DC
- Dimensions: 4"W x 1"H x 3.25"D
- Shipping Weight: 2 lbs.