

TVlogic LVM-212W(3G) 21.5 inch Composite/Component/3G-SDI/DVI/HDMI

1920x1080 19 inch Rack-size LCD Monitor

LVM-212W is an ideal rack-mount monitor for video wall in control rooms and OB Vans. Inside the beautiful slim bezel design that just fits into a 19" rack, integrated the wide viewing angle LCD panel with native Full HD resolution and 16.7M colors and TVLogic's unique video processing technology that enables high picture quality 3G-SDI and all the professional features.

Features

- Compatible with various SDI signals formats (SD/HD/3G)
 - This product is compatible with various SDI signals
 - SD/HD/3G(A/B)
 - SDI 480i,576i,720p,1080i/p,1080psf
- Compatible with various Analog signals
 - This product is compatible with various analog signals such as CVBS(Composite), S-Video, YPbPr(Component) and RGB.
- HDMI/ DVI Digital(HDCP)/ DVI Analog function built-in
 - HDMI, DVI Digital(HDCP) and DVI Analog(VGA) Inputs are available without any additional accessory.
- All-in-one type system
 - Slim and all-in-one type monitor that requires no other accessory, for optimized space utilization.
- Waveform/Vectorscope/Audio Level Meter Function
 - Waveform & Vectorscope.
 - Embedded Audio Level Meter.
- Luma(Yâ™) zone check(Color/Zebra type)/ Range error Function
- Audio in & out
 - Internal Speaker(activates only with input signals with Embedded Audio)
 - Stereo Audio Out & External Audio In through phone Jack.
- BLUE ONLY/MONO/Focus-Assist/H/V delay
- Internal pattern generator(0~100% Gray/ Colorbar+Pluge)
- Various Markers & Safety Areas
 - Center Marker, Safety Area Marker, Aspect Marker, Display Size(Scan)
- Knob Control
 - Easy to adjust user configuration using the control Knob on the front of the monitor.
- 1:1 SCAN / Zoom
 - 1:1 SCAN : Used to display the original image resolution without scaling to match a certain resolution or an aspect ratio.
 - Zoom: Used to enlarge the original image.
 - Zoom Scroll Function (Left/Right, Top/ Bottom)
- Wide screen compatible
 - Native 16:9 Wide Screen (LVM-212W)
- External control function
 - This product can be controlled by using parallel switch, RS-422 and Network simply with cable connection without additional peripheral equipment attached to the unit.
- RS422/UMD feature support
 - This product supports protocols provided by TVLogic or a TSL protocol.
- AC/DC Compatible
 - Basically, this product is powered by normal AC power source and can also be powered by DC 24V as well.
- Additional Features
 - Wide Viewing Angle, Loop Through (SDI/ Analog), VESA Mounting Standard, Contrast Ratio of 1000:1, 365 cd/m2 OSD user interface and Rack Mountable.